REPORT

Tonkin+Taylor

Orchard/Orphanage hydraulic model update

Prepared for Nelson City Council Prepared by Tonkin & Taylor Ltd Date June 2022 Job Number 870888.0013 v1





Document control

Title: Orchard/Orphanage hydraulic model update					
Date	Version	Description	Prepared by:	Reviewed by:	Authorised by:
16/06/2023	1	First issue	K Beckett	D Velluppillai	D Velluppillai

Distribution:

Nelson City Council Tonkin & Taylor Ltd (FILE)

1 electronic copy 1 electronic copy

Table of contents

1	Introduction		1
2	Mod	Model updates	
	2.1	Hydrological model	2
	2.2	Hydraulic model	4
3	Applicability		8
Арр	endix A	Model schematic	
Арр	endix E	2D roughness values	
App	endix (Hydraulic structures	

- Appendix D Model results
- Appendix E Peer review table

1 Introduction

Tonkin & Taylor Ltd (T+T) has been engaged by Nelson City Council (NCC) to update the existing Orchard and Orphanage Streams hydraulic model.

WSP previously reviewed the Orchard/Orphanage hydraulic model (version 202007 v32) in January 2021. Refer WSP's memorandum "Final Peer Review of T&T Orchard-Orphanage Catchment Model Update", 11 January 2022.

NCC has since requested that updates be made to the hydraulic model in preparation for a proposed Housing Plan Change in 2023.

This work is needed to maintain confidence in model results by including latest data and information. It is limited to what can be achieved in the available timeframes, with a number of future model improvements identified for the next release. A model version history is provided for context in Table 1.1 below.

The work has been undertaken under our conditions of engagement, Professional Services Brief Variation Order 15 dated 20 March 2023, T+T ref: 870888.0013.

Hydrologic model version	Description		
	 The models were originally built by MWH (now Stantec) in 2016 as separate "Orchard" and "Orphanage" catchment models under the "Nelson Urban Stream Flood Modelling" (MWH, June 2016). 		
Source models	 Stantec supplied the Orphanage model to Tonkin & Taylor Ltd (T+T) in 2017 for the purpose of representing a culvert upgrade at Saxton Road East and bunding in the Saxton Reserve. 		
HEC-HMS	• Stantec updated the Orchard model with HIRDs v4 rainfall data and MfE's updated climate change scenarios in 2019/2020.		
	 Following this update, the Orchard model was handed over to T+T in July 2020 for the purpose of combining with the Orphanage model to create a single combined model. 		
202007v1	• This was the first peer reviewed version of the combined catchment model. Peer review was provided by WSP.		
HEC-HMS	 Hydrologic model used for Nelson Urban Streams hydraulic modelling project (July 2021). 		
202205∨5 MIKE by DHI	• Hydrological schematisation approach updated with "overland flowpath" and "split-flow" subcatchments to improve modelling of overland flowpaths across the range of design events.		
	• This model version is described as part of this model update report.		
Hydraulic model version	Description		
	 The models were originally built by MWH (now Stantec) in 2016 as separate "Orchard" and "Orphanage" flood models under the "Nelson Urban Stream Flood Modelling" (MWH, June 2016). 		
Source model MIKE by DHI	 Stantec provided the Orphanage model to Tonkin & Taylor Ltd (T+T) in 2017 for the purpose of representing a culvert upgrade at Saxton Road East and bunding in the Saxton Reserve. 		
	• Stantec updated the Orchard model with HIRDs v4 rainfall data and MfE's updated climate change scenarios in 2019/2020.		

	• Following this update, the Orchard model was handed over to T+T in July 2020 for the purpose of combining with the Orphanage model to create a single combined model.
OrchOrph_202007v32 MIKE by DHI	 This was the first peer reviewed version of the combined flood model. Peer review was provided by WSP. Hydraulic model used for Nelson Urban Streams hydraulic modelling project (July 2021).
OrchOrph_202210_V19 MIKE by DHI	 Hydraulic model schematisation, terrain data and vertical datum updated. This model version was issued to WSP for peer review on 22/11/2022.
OrchOrph_202210_V20 MIKE by DHI	 Updates to hydraulic model following peer review comments (WSP, 14/12/2022). This model version is described as part of this model update report.

2 Model updates

2.1 Hydrological model

This memo refers to the latest hydrological model, version: 202205v5.

The hydrological model has been updated since the last peer-reviewed version. The update affects the delineation of some subcatchments, and maximum subcatchment rates of discharge to Orchard Stream, as described below. Base catchment loss parameters based on existing land-use and design rainfall data remain unchanged.

Runoff during rainfall events is conveyed through an urban catchment via a combination of the pipe network (**primary system**) and overland flowpaths (**secondary system**, typically including sheet flow, open drains, kerb and channels and watercourses). In Nelson, the design standard for capacity of new pipes is conveyance of the 2090 RCP8.5 6.67% AEP¹ flow. In larger events (and/or where pipes are currently undersized), any flow in excess of this capacity is conveyed overland. That is, during extreme events, runoff is often split between piped and overland flow, with the split amount governed by the capacity of the pipe network.

Secondary flowpaths often follow similar alignments to the primary (piped) network within a catchment. However, depending on topography and network layout for a given subcatchment, it is not uncommon for the piped component of a catchment's runoff to enter a receiving watercourse (e.g. Orchard Stream) at a different location to the overland flow component.

Orchard Stream subcatchments were previously delineated based on the piped stormwater network system. This assumed that <u>all</u> runoff from the subcatchment is conveyed into the Orchard Stream at the pipe discharge point, whether via pipe or overland flow. This is a reasonable approximation for some subcatchments, but less so for others. For some subcatchments within the urban area of the Orchard Stream catchment, the primary network conveys flows towards Orchard Stream, while flows in excess of the primary (piped) system capacity are expected to be conveyed overland away from Orchard Stream. Thus, an assumption that both the primary and overland flow catchments both discharge to the stream at the pipe outlet point in the stream is likely to lead to an overestimation of flows at that point in the stream. This was discussed with NCC and the following approach agreed:

1 Identify locations where overland flowpaths are expected to flow away from Orchard Stream (based on topography) while the stormwater pipe network drains to Orchard Stream ('split-flow' subcatchments).

¹ Annual Exceedance Probability

- 2 Undertake hydrological modelling of these subcatchments to generate runoff hydrographs for design events, as per previous modelling.
- 3 The resulting runoff hydrographs from split-flow subcatchments are then capped at the maximum capacity of the outlet pipes (based on free full flow hand calculation). These are referred to as 'urban-only' subcatchments within the hydrological model, i.e. only runoff from the urban stormwater pipe network is included.
- 4 The residual flows would in reality follow overland flowpaths from the exceeded pipe intake location, according to local topography. However, as the focus of this model is on understanding flooding associated with river outbreak rather than pipe network capacity exceedance, NCC has elected not to add these residual flows to the 2d model. This means that any flooding due to this exceedance will be not represented in this model. This flooding would instead be represented in NCC's separate stormwater model.

Table 2.1 below outlines the updates made to the hydrological model (version 202205v5).

Table 2.1:	Hydrological	model	updates
------------	--------------	-------	---------

Ref.		Model update (202205v5)	
	Subcatchments	 LiDAR used to generate subcatchments and indicative overland flowpath directions via GIS process. Model subcatchments re-digitised based on: 	
1		 Those flowing directly into stream Those flowing away from stream but pipe network flows into stream (named 'split-flow' subcatchments). 	
		 Note that this results in a small overlap in subcatchments where pipe network flows into Orchard Stream but overland flowpath flows in Orphanage Stream (or vice versa). 	
		Longest flowpaths re-digitised.	
2	Hydrological parameters	 Hydrological parameters (CN, lag time) recalculated as per previous methodology. 	
3 Rair	Rainfall	 HIRDs v4 reports regenerated from approximate centroid of updated sub-catchments. 	
		 Hyetographs regenerated as per previous methodology. 	
		 Hydrological model converted from HEC-HMS to Mike Urban. This change improves the model as follows: 	
4	I hadwala staal	 Same software as hydraulic model 	
	model	 Sits with hydraulic model 	
		 Easier to update storm scenarios 	
		 Run at 1 minute intervals (compare 5 minute intervals previously) to improve resolution. 	

Ref.		Model update (202205v5)		
5	Runoff transform	 Runoff flows from the 'split-flow' subcatchments are transformed from the Mike Urban hydrology output (crf) file as follows: Theoretical capacity of 'split-flow' subcatchments' outlet pipe is calculated assuming free full flow Slope is calculated using inverts from Top of the South Maps Where upstream/downstream inverts are not known, a slope of 1% is assumed Runoff flow from the hydrological model is capped to the outlet pipe capacity for the 'split-flow' subcatchments Transformed runoff is exported to dfs0 format ready for loading in to the hydraulic model. Note that sensitivity tests of the assumed pipe slope indicates that the absolute error associated with this not significant compared to the overall catchment flows. 		
6	Runoff loading	 Loading locations of the runoff are updated based on the updated s ub-catchments. Location is based on GIS-generated overland flowpaths. 		

2.2 Hydraulic model

This memo refers to the latest hydraulic model, version: OrchOrph_202210_V20

The hydraulic model has been updated since the last reviewed version.

Generally, updates have incorporated the following:

- Update of terrain from 2015 to 2021 LiDAR
- Addition of recently constructed flood protection works (stopbanks and flood walls) at Orphanage Stream
- Refinement of 1D channel/2D mesh extents
- Update of vertical datum from NCC Vertical Datum to NZVD2016.

Updates that were not carried out and are flagged for future model improvements include the following:

- Software upgrade to MIKE+
- Incorporation of Saxton Creek. Currently, the Orphanage Stream flood extents interact with Saxton Creek. No allowances have been made for any interaction of flood flows between Orphanage Stream and Saxton Creek. Orphanage Stream outbreak flooding is artificially constrained in the model beyond (south of) Saxton Creek, as can be seen in the 2D model results. Results in this area are considered inaccurate; this area is expected to be covered in a separate model for the Saxton Creek catchment (although there is hydraulic interaction). Issued model results are therefore trimmed at Saxton Creek for the purposes of this flood mapping exercise.
- Adjustment of sea level rise values to incorporate NZSeaRise/VLM data. Current values (1.11 m to 2130 RCP8.5M) are based on MfE 2017.
- The tidal boundary is not represented in the 2D model as "bathtub modelling" of coastal inundation shows that the highest design tide level including projected sea level rise is not expected to overtop the state highway, which effectively acts as a flood barrier. Results downstream of the highway (i.e. in the estuary) are not considered accurate and will be trimmed in post-processing.

- Use of August 2021 and August 2022 observations (flood levels, rain radar and rainfall/flow gauge data) to recalibrate the hydrological and hydraulic models.
- Inclusion of new Orchard Stream culvert at approx. chainage 1,450 m (at 42 Curtis Street).
- LiDAR resolution at Orphanage North is very poor. 1D channel extents purposefully kept wide so that refinement can more easily be made in later stages. It is recommended that survey is obtained for this heavily vegetated area and incorporated into the model.

Ref.	Previous model (202007_v32)		Updated model (202210_V20)		
1	General information	 Orchard Stream and Orphanage Stream Coordinate system: NZTM 2000 Vertical Datum: NCC Datum Base tidal condition: MHHW (1.21 mRL) 	 Orchard Stream and Orphanage Stream Coordinate system: NZTM 2000 Vertical Datum: NZVD2016 Base tidal condition: MHHW (1.21 mRL) 		
2	Software	• MIKE by DHI 2017 (flexible mesh)	unchanged		
3	2D digital elevation model	• 2015 LiDAR	 2021 LiDAR 2021 Orphanage flood protection works (source: as-builts). Incorporated through use of dikes, mesh level adjustment and changes to cross section bank levels. 		
4	2D mesh size	 Constant mesh: Mesh elements <10 m³ (sides typically <5 m). Refinement mesh area – Railway reserve: Mesh elements < 5 m². 	 River mesh arcs (1D extent): 1 m spacing. Road mesh arcs: 4 m spacing. Mesh boundary extent arc: 8 m spacing. 		
5	2D roughness	 Methodology unchanged from original models built by MWH (now Stantec) in 2016. This applies roughness values based on NCC Planning Zones. Roughness map extended to cover both Orchard and Orphanage Streams. Refer to Appendix B for 2D roughness values. 	• unchanged		
6	1D river	 <u>Centreline</u> Centreline unchanged from original models built by MWH (now Stantec) in 2016. <u>Cross sections</u> Cross section data source 1: 2015 survey (ID recorded as 'CHxx' in cross sections file). Cross section data source 2: 2015 LiDAR (ID recorded as 'GISxx' in cross sections files). 	 <u>Centreline</u> Centreline adjusted using 2021 LiDAR. Note that changes mainly apply to upstream branches of Orphanage Stream. <u>Cross sections</u> Cross section data source 1: 2021 LiDAR cross sections cut at approximately 10 m intervals. Cross section data source 2: cross sections are updated to include Orphanage flood protection works 		

Table 2.2: Hydraulic model updates

Ref.		Previous model (202007_v32)	Updated model (202210_V20)	
		 Note that there was significant distance between cross sections in these models. 	 (stopbanks and flood walls) where they lie within the 1D extent. Cross section data source 3: 2015 survey cross sections are retained in the model. <u>River 'no mesh' extent</u> 1D river extent is refined using a combination of 2021 LiDAR cross sections, property boundaries and previous results. 	
7	1D (river) roughness	 Manning's n = 0.045 (following analysis of flooding and flows at Suffolk Road Bridge). 	unchanged	
8	1D structures	• Refer structures table provided in Appendix C.	 Structures unchanged but converted to NZVD2016. Addition of floodplain culvert at Storage World using as-builts provided by NCC. Addition of culvert upstream of Nikau Street following peer review comments on V19 of the model. Asbuilts were provided by NCC. Manning's n roughness of concrete structures updated from n = 0.013 to n = 0.015. Refer structures table provided in Appendix C. 	
9	1D stormwater network	 Orchard Stream is piped for a portion. This is modelled in Mike Urban. 	 Concrete roughness is reduced from n = 0.019 to n = 0.015 following peer review comments on V19 of the model. Urban network is simplified from previous model version due to instabilities. Simplification 1 –portion of Orchard Stream that is supposed to daylight between 7A/7B Titoki Street is ignored. 900mm dia. pipe is assumed to connect right through. No information about daylighting portion. Unstable when represented as open channel. Simplification 2 – network is simplified (pipes merged) where grade is constant and manhole is shown not to spill in 1 hour duration testing (critical duration). 	
10	1D/2D coupling		 Mike urban spilling is reduced to a maximum flow of 0.05 m³/s on the assumption of 2 catchpits being connected for each manhole. 	

Ref.		Previous model (202007_v32)	Updated model (202210_V20)
			 Orphanage Flood Protection works (2021) have a stopbanks and flood walls. The flood wall is very narrow and therefore represented in MIKE 11. Coupling at lateral link is therefore set to M11. Note that a dike in MIKE 21 at the upstream end is used to represent the flood wall return and prevent flows getting around the back of the wall at the upstream end. Portion of Orchard stream that is supposed to daylight at 5 Polstead is coupled to M21 via centreline. Google streetview indicates an open drain is possible but uncertain at this location.
11	Calibration/ validation		 A preliminary validation exercise was undertaken using the August 2021 event. Note that the 5th – 6th August 2021 event was a relatively small event (approximately a 0.2 AEP "5 year" event). The scenario results confirmed modelled manning's n values are generally appropriate, and no changes to the model were made as a result.

3 Applicability

This report has been prepared for the exclusive use of our client Nelson City Council, with respect to the particular brief given to us and it may not be relied upon in other contexts or for any other purpose, or by any person other than our client, without our prior written agreement.

Tonkin & Taylor Ltd Environmental and Engineering Consultants

.....

Report prepared by:

Authorised for Tonkin & Taylor Ltd by:

Kelseng Rechett

Kelsey Beckett Water Resources Engineer

Damian Velluppillai Project Director

KBBB

.

p:\870888\870888.0013\issueddocuments\2023-06-16 - to ncc - orchorph model update report\orchorph hydraulic model update.v1.kbbb.20230615.docx

















Appendix B 2D roughness values

Excerpt from original model build report Nelson Urban Streams Flood Modelling Final Report, MWH, June 2016:

Land Use Zone	Classification	Mannings n roughness Adopted for Parcels Excluding Building
CLA	Open Space	0.045
CONSVTN	Open Space	0.045
IC_CENTRE	Industrial/Commercial	0.1
IC_FRINGE	Industrial/Commercial	0.1
IC_INTDEV	Industrial/Commercial	0.1
IND	Industrial/Commercial	0.1
IND_NS	Industrial/Commercial	0.1
OS_REC	Open Space	0.045
RES	Urban Residential	0.09
RES_HI	Urban Residential	0.09
RES_LO	Urban Residential	0.09
RES_LO_NS	Urban Residential	0.09
ROAD	Road	0.02
RURAL	Rural	0.045
RURAL_HI_SH	Rural	0.045
RURAL_LO_SH	Rural	0.045
STRM	Open Space	0.045
SUB COM	I Industrial/Commercial	0.1

Table 4-1: 2D Model Roughness Values

Orchard Stream/Orphanage Stream catchment model

1D Hydraulic Structures

HYDRAULIC STRUCTURES SUMMARY: OrchOrph_202210_V20

River and Structure ID	Structure Name	Physical location	Modelled	structure type
			Structure	Overflow ¹
Orchard Stream 1	SongerStCulvert Added by T+T in model version OrchOrph_202007_v03. Not previously modelled.	Intersection of Songer Street and The Ridgeway	MIKE 11 culvert	Represented in 2D model
Orchard Stream 2	TainuiStDiversionCulvert Added by T+T in model version OrchOrph_202210_v20. Not previously modelled.	35 Nikau Street	MIKE 11 culvert	MIKE 11 weir
Orchard Stream 3	NikauRdCulvert	30 / 35 Nikau Street	MIKE 11 culvert	MIKE 11 weir
Orchard Stream 4	11PolsteadCulvert Added by T+T in model version OrchOrph_202007_v03. Not previously modelled.	11 Polstead Road	MIKE 11 culvert	MIKE 11 weir
Orchard Stream 5	-	Driveway over stream at 9 Polstead Road	Not modelled	Not modelled
Orchard Stream 6	-	Stream crossing at 7a Polstead Road	Not modelled	Not modelled
Orchard Stream 7	5PolsteadCulvert	5 Polstead Road / 639 Main Road Stoke	MIKE 11 culvert	Represented in 2D model
Orchard Stream 8	OrchMainRdStokeCulvert	632 / 639 Main Road Stoke	MIKE 11 culvert	Represented in 2D model
Orchard Stream 9		Shared pathway stream crossing at Railway Reserve near Byron Lane	Not modelled	Not modelled
Orchard Stream 10	MarloweStCulvert	Marlowe Street	MIKE 11 culvert	MIKE 11 weir
Orchard Stream 11	NaylandRdCulvert	Nayland Road	MIKE 11 culvert	Represented in 2D model
Orchard Stream 12	CurtisStCulvert To be surveyed and added in next model iteration	Stream crossing between Curtis Street and Monaco View	MIKE 11 culvert	Not modelled
Orchard Stream 13a	OrchWhakatuDrCulvert_RightBox	Whakatu Drive / SH6	MIKE 11 culvert	Represented in 2D model
Orchard Stream 13b	OrchWhakatuDrCulvert_LeftBox	Whakatu Drive / SH6	MIKE 11 culvert	Represented in 2D model
Orphanage North 1		East/downstream of Huntaway Close	Not modelled	Not modelled
Orphanage North 2		East/downstream of Huntaway Close	Not modelled	Not modelled
Orphanage North 3	MontebelloCulvert	Montebello Avenue / Ngawhatu Road	MIKE 11 culvert	Represented in 2D model
Orphanage South 1		Stream (farm) crossing at 467 Suffolk Road	Not modelled	Not modelled
Orphanage South 2		Stream (farm) crossing at 70 Sunningdale Drive	Not modelled	Not modelled
Orphanage South 3		Stream crossing at 70 Sunningdale Drived, access across from 28 Sunningdale Drive	Not modelled	Not modelled
Orphanage South 4	WoodfordCulvert	Woodford Lane	MIKE 11 culvert	MIKE 11 weir
Orphanage South 5a	BridgewaterCulvert1	Bridgewater Lane	MIKE 11 culvert	MIKE 11 weir
Orphanage South 5b	BridgewaterCulvert2	Bridgewater Lane	MIKE 11 culvert	MIKE 11 weir
Orphanage South 6		Orphanage Stream esplanade reserve crossing between 5 Montebello Avenue and 15 Bridgewater Lane	Not modelled	Not modelled
Orphanage South Tributary 1	BridgewaterCulvert3	9 / 26 Bridgewater Lane	MIKE 11 culvert	Represented in 2D model
Orphanage South Tributary 2		Stream crossing 7 Bridgewater Lane	Not modelled	Not modelled
Orphanage Stream 1	SuffolkRdCulvert	321 /324 Suffolk Road	MIKE 11 culvert	Represented in 2D model
Orphanage Stream 2		Orphanage Lane stream crossing	Not modelled	Not modelled

River and Structure ID	Structure Name	Physical location	Modelled s	tructure type
			Structure	Overflow ¹
Orphanage Stream 3		Orphanage Stream crossing between Woodstock Place and Gershwin Grove	Not modelled	Not modelled
Orphanage Stream 4a	SaxtonRdCulvert	117 Saxton Road	MIKE 11 culvert	MIKE 11 weir
Orphanage Stream 4b	SaxtonRdCulvert2018	117 Saxton Road	MIKE 11 culvert	MIKE 11 weir
Orphanage Stream 5		Orphanage Stream crossing at Saxton Way, Saxton Fields	Not modelled	Not modelled
Orphanage Stream 6	SaxtonFieldPondWeir	Pond at Saxton Field, immediately upstream of Saxton Road	MIKE 11 weir	n/a
Orphanage Stream 7a	OrphMainRdStokeCulvert1	Main Road Stoke near 9 Tokomaru Place	MIKE 11 culvert	Represented in 2D model
Orphanage Stream 7b	OrphMainRdStokeCulvert2	Main Road Stoke near 9 Tokomaru Place	MIKE 11 culvert	Represented in 2D model
Orphanage Stream 8		Stream crossing at Elms Street	Not modelled	Not modelled
Orphanage Stream 9a	OrphWhakatuDrCulvert1	Whakatu Drive/ SH6 near 23 Elms Street	MIKE 11 culvert	Represented in 2D model
Orphanage Stream 9b	OrphWhakatuDrCulvert2	Whakatu Drive/ SH6 near 23 Elms Street	MIKE 11 culvert	Represented in 2D model
Floodplain 1	WhakatuEstateCulvert	23 Elms Street to estuary	MIKE 11 culvert	Represented in 2D model

1: Culvert overtopping within the 1D model is typically represented as a MIKE 11 weir. This is true when the structure is located at a crest or sag in the road. Overtopping is represented in the 2D model where there is the potential for flows across the road / perpendicular to the channel.

MODELLED MIKE 11 CULVERTS: OrchOrph_202210_V20

River and Structure ID	Structure Name	Physical location	Modelled structure type	Upstream IL (mRL, NZVD2016 ³)	Data Source: USIL	Downstream IL (mRL, NZVD2016 ³)	Data Source: DSIL	No. barrels Shape Geometry Valve regulation	Data source: barrels/geometry	Length (m)	Data source: length	Manning's n	Data source: Material and roughness
Orchard Stream 1	SongerStCulvert Added by T+T in model version OrchOrph_202007_v03. Not previously modelled	Intersection of Songer Street and The Ridgeway	MIKE 11 culvert	42.343	Modelled cross section invert, which is interpolated from 2015 LiDAR cross sections. Note that this level is consistent with 2021 LiDAR also.	41.55	Modelled cross section invert, which taken from 2021 LiDAR cross sections.	1x Circular 0.90 m dia.	TOTSM ¹	12.2	TOTSM ¹	0.015	Concrete (TOTSM ¹)
						41.99	Modelled cross section invert, which taken from interpolated 2015 LiDAR cross sections.						
Orchard Stream 2	TainuiStDiversionCulvert Added by T+T in model version OrchOrph_202210_v20. Not previously modelled.	35 Nikau Street	MIKE 11 culvert	16.75	As-builts NCC Plan No: 26-0634 23/11/2001	16.72	As-builts NCC Plan No: 26-0634 23/11/2001	1x Circular 0.9 m dia.	As-builts NCC Plan No: 26- 0634 23/11/2001	2.44	As-builts NCC Plan No: 26-0634 23/11/2001	0.015	Concrete (As- builts)
Orchard Stream 3	NikauRdCulvert	30 / 35 Nikau Street	MIKE 11 culvert	16.81	Orchard model received from Stantec ²	16.65	Orchard model received from Stantec ²	2x Circular 1.35 m dia.	Orchard model received from Stantec ²	18.8	TOTSM ¹	0.015	Orchard model received from Stantec ²
Orchard Stream 4	11PolsteadCulvert Added by T+T in model version OrchOrph_202007_v03. Not previously modelled.	11 Polstead Road	MIKE 11 culvert	15.63	Modelled cross section invert, which is interpolated from 2015 surveyed and 2015 LiDAR cross sections	15.60	Modelled cross section invert, which is interpolated from 2015 surveyed and 2021 LiDAR cross sections	1x Circular 1.35 m dia.	TOTSM ¹	11.6	TOTSM ¹	0.015	Concrete (TOTSM ¹)
						15.527	Modelled cross section invert, which is interpolated from 2015 surveyed and 2015 LiDAR cross sections						
Orchard Stream 7	5PolsteadCulvert	5 Polstead Road / 639 Main Road Stoke	MIKE 11 culvert	14.79	Orchard model received from Stantec ²	14.66	Orchard model received from Stantec ²	1x Circular 1.35 m dia.	Orchard model received from Stantec ²	27.6	TOTSM ¹	0.015	Orchard model received from Stantec ²
Orchard Stream 8	OrchMainRdStokeCulvert	632 / 639 Main Road Stoke	MIKE 11 culvert	14.8	Orchard model received from Stantec ²	13.65	Orchard model received from Stantec ²	1x Rectangular 1.07 W x 1.30 H m	Orchard model received from Stantec ²	44.8	TOTSM ¹	0.015	Orchard model received from Stantec ²
Orchard Stream 10	MarloweStCulvert	Marlowe Street	MIKE 11 culvert	9.0	Orchard model received from Stantec ²	8.91	Orchard model received from Stantec ²	1x Rectangular 3.00 W x 1.80 H m	Orchard model received from Stantec ²	14.2	TOTSM ¹	0.015	Orchard model received from Stantec ²
Orchard Stream 11	NaylandRdCulvert	Nayland Road	MIKE 11 culvert	6.63	Orchard model received from Stantec ²	6.45	Orchard model received from Stantec ²	1x Rectangular 4.60 W x 1.79 H m	Orchard model received from Stantec ²	15.4	TOTSM ¹	0.015	Orchard model received from Stantec ²
Orchard Stream 12	CurtisStCulvert	Curtis Street / Manaco View	MIKE 11 culvert		·		To b	e added in next mode	el version				
Orchard Stream 13a	OrchWhakatuDrCulvert_Ri ghtBox	Whakatu Drive / SH6	MIKE 11 culvert	0.78	Orchard model received from Stantec ²	0.77	Orchard model received from Stantec ²	1x Rectangular 3.70 W x 2.04 H m	Orchard model received from Stantec ²	34.4	TOTSM ¹	0.015	Orchard model received from Stantec ²

River and Structure ID	Structure Name	Physical location	Modelled structure type	Upstream IL (mRL, NZVD2016 ³)	Data Source: USIL	Downstream IL (mRL, NZVD2016 ³)	Data Source: DSIL	No. barrels Shape Geometry Valve regulation	Data source: barrels/geometry	Length (m)	Data source: length	Manning's n	Data source: Material and roughness
Orchard Stream 13b	OrchWhakatuDrCulvert_Le ftBox	Whakatu Drive / SH6	MIKE 11 culvert	1.1	Orchard model received from Stantec ²	0.81	Orchard model received from Stantec ²	1x Rectangular 3.70 W x 1.80 H m	Orchard model received from Stantec ²	34.4	TOTSM ¹	0.015	Orchard model received from Stantec ²
Orphanage North 3	MontebelloCulvert	Montebello Avenue / Ngawhatu Road	MIKE 11 culvert	36.02	Orphanage model received from Stantec ²	35.65	Orphanage model received from Stantec ²	1x Rectangular 3.70 W x 1.80 H m	Orphanage model received from Stantec ²	17.6	TOTSM ¹	0.015	Orphanage model received from Stantec ²
Orphanage South 4	WoodfordCulvert	Woodford Lane	MIKE 11 culvert	42.63	Orphanage model received from Stantec ²	42.55	Orphanage model received from Stantec ²	1x Circular 1.80 m dia.	Orphanage model received from Stantec ²	13.7	TOTSM ¹	0.015	Orphanage model received from Stantec ²
Orphanage South 2a	BridgewaterCulvert1	Bridgewater Lane	MIKE 11 culvert	35.3	Orphanage model received from Stantec ²	34.8	Orphanage model received from Stantec ²	1x Circular 1.50 m dia.	Orphanage model received from Stantec ²	25.1	TOTSM1	0.015	Orphanage model received from Stantec ²
Orphanage South 2b	BridgewaterCulvert2	Bridgewater Lane	MIKE 11 culvert	38.6	Orphanage model received from Stantec ²	36.78	Orphanage model received from Stantec ²	1x Circular 1.05 m dia.	Orphanage model received from Stantec ²	25.1	TOTSM ¹	0.015	Orphanage model received from Stantec ²
Orphanage South Tributary 1	BridgewaterCulvert3	9 / 26 Bridgewater Lane	MIKE 11 culvert	38.8	Orphanage model received from Stantec ²	38.41	Orphanage model received from Stantec ²	1x Circular 1.20 m dia.	Orphanage model received from Stantec ²	24.2	TOTSM ¹	0.015	Orphanage model received from Stantec ²
Orphanage Stream 1	SuffolkRdCulvert	321 /324 Suffolk Road	MIKE 11 culvert	22.827	T+T onsite measurements as per TUFLOW 2D Suffolk bend model (#1006675.0420)	22.547	T+T onsite measurements as per TUFLOW 2D Suffolk bend model (#1006675.0420)	1x Rectangular 8.7 W x 2.20 H m	T+T onsite measurements as per TUFLOW 2D Suffolk bend model (#1006675.0420)	13	TOTSM ¹	0.015	T+T onsite measurements as per TUFLOW 2D Suffolk bend model (#1006675.0420)
			MIKE 11 culvert	22.63	Extracted from bridge structure in Orphanage model received from Stantec ²	22.61	Extracted from bridge structure in Orphanage model received from Stantec ²	1x Irregular level- width table (A). Note that default head loss factors are changed to 0.1, 0.1, 1.0, 0.0	Extracted and modified from bridge structure in Orphanage model received from Stantec ²	11.2	Extracted from bridge structure in Orphanage model received from Stantec ²	0.015	Modified from bridge structure in Orphanage model received from Stantec ²
			FHWA WSPRO bridge (submergence only)	22.621	Orphanage model received from Stantec ²	22.621	Orphanage model received from Stantec ²	1x Bridge x-z table (B) <i>With zero slope.</i> Soffit at 37.051 mRL	Orphanage model received from Stantec ²	11.2	Orphanage model received from Stantec ²	0.0143	Orphanage model received from Stantec ²
Orphanage Stream 4a	SaxtonRdCulvert	117 Saxton Road	MIKE 11 culvert	7.3	Orphanage model received from Stantec ²	7.12	Orphanage model received from Stantec ²	1x Rectangular 5.93 W x 2.03 H m	Orphanage model received from Stantec ²	16.0	TOTSM ¹	0.015	Orphanage model received from Stantec ²
Orphanage Stream 4b	SaxtonRCulvert2018	117 Saxton Road	MIKE 11 culvert	7.3	Orphanage model received from Stantec ²	7.12	Modified from Orphanage model received from Stantec ²	1x Rectangular 5.0 W x 2.0 H m	As-builts	16.0	TOTSM ¹	0.015	Orphanage model received from Stantec ²

River and Structure ID	Structure Name	Physical location	Modelled structure type	Upstream IL (mRL, NZVD2016 ³)	Data Source: USIL	Downstream IL (mRL, NZVD2016 ³)	Data Source: DSIL	No. barrels Shape Geometry Valve regulation	Data source: barrels/geometry	Length (m)	Data source: length	Manning's n	Data source: Material and roughness
	Same culvert as above, called "Saxton Road Culvert 2". Proposed culvert at time of model build, now built.		MIKE 11 culvert	7.3	Orphanage model received from Stantec ²	7.1	Orphanage model received from Stantec ²	1x Rectangular 5.0 W x 2.0 H m	Orphanage model received from Stantec ²	16.9	Orphanage model received from Stantec ²	0.013	Orphanage model received from Stantec ²
Orphanage Stream 7a	OrphMainRdStokeCulvert1	Main Road Stoke near 9 Tokomaru Place	MIKE 11 culvert	3.94	Orphanage model received from Stantec ²	3.96	Orphanage model received from Stantec ²	1x Rectangular 3.6 W x 1.9 H m	Orphanage model received from Stantec ²	20.2	TOTSM ¹	0.015	Orphanage model received from Stantec ²
Orphanage Stream 7b	OrphMainRdStokeCulvert2	Main Road Stoke near 9 Tokomaru Place	MIKE 11 culvert	4.02	Orphanage model received from Stantec ²	3.93	Orphanage model received from Stantec ²	1x Rectangular 4.12 W x 2.25 H m	Orphanage model received from Stantec ²	20.2	TOTSM ¹	0.015	Orphanage model received from Stantec ²
Orphanage Stream 9a	OrphWhakatuDrCulvert1	Whakatu Drive/SH6 near 23 Elms Street	MIKE 11 culvert	1.3	Orphanage model received from Stantec ²	1.22	Orphanage model received from Stantec ²	1x Rectangular 5.91 W x 2.85 H m	Orphanage model received from Stantec ²	32.8	TOTSM ¹	0.015	Orphanage model received from Stantec ²
Orphanage Stream 9b	OrphWhakatuDrCulvert2	Whakatu Drive/SH6 near 23 Elms Street	MIKE 11 culvert	2.12	Orphanage model received from Stantec ²	2.03	Orphanage model received from Stantec ²	1x Rectangular 3.9 W x 2.05 H m	Orphanage model received from Stantec ²	32.8	TOTSM ¹	0.015	Orphanage model received from Stantec ²
Floodplain 1	WhakatuEstateCulvert	23 Elms Street to estuary	MIKE 11 culvert	1.376	As-builts NCC Plan No: 26-0802 01/10/2021	0.786	As-builts NCC Plan No: 26-0802 01/10/2021	1x Circular 1.00 m dia.	As-builts NCC Plan No: 26- 0802 01/10/2021	38.0	As-builts NCC Plan No: 26-0802 01/10/2021	0.009	Roughness value for GRP pipe, retrieved https://grandpipe .com/en/product- information

1: TOTSM = Top of the South Maps

The Orchard and Orphanage models were originally built by MWH in 2016 (now Stantec). These were two separate models. As part of the model build, Staig & Smith undertook survey of structures in 2015. However, the total number of structures and the reported number of survey carried out is inconsistent. This means that it is unclear whether specific structures have or have not been surveyed. For the purpose of the flood modelling, it is assumed that structure information in the received models is accurate (i.e. likely from survey) unless there are inconsistencies with surrounding data. These models represented concrete structures with a roughness of Manning's n=0.013. Concrete roughness has been set to a consistent and slightly higher roughness of n=0.015 to account for aging of infrastructure in V20.
 Models were originally built to NCC vertical datum. (NCC datum has a 12.07 m vertical offset from Nelson Vertical Datum NVD-55). To convert structure invert levels from source NCC datum to NZVD2016, a 12.4 m offset is applied (NZVD2016 = NCC Datum – 12.4), i.e. NZVD2016 levels are lower.

Additional culvert geometry data:

Reference	Structure	Structure data (NCC Datum)	Figure
A	Suffolk Road culvert: irregular level-width table	35.021 0 35.204 3.43 35.608 7.435 35.94 8.472 37.051 8.472	Instituture: Orphanage Stream - 417.0000 - Suffolk Road Cross Section: Orphanage Stream - NCC Flood Modelling 37.0
В	Suffolk Road bridge: irregular level-width table	0 37.051 0 35.608 3.987 35.021 6.174 35.204 8.474 35.94 8.474 37.051	Interestructure: Orphanage Stream - 417.0000 - Suffolk Rd Cross Section: Orphanage Stream - NCC Flood Modellin 37.5 37.0 36.5 36.0 36.0 36.5 36.0 36.5 36.0 36.0 36.0 36.5 36.0 36.5 36.0 36.5 36.0 36.5 36.0 36.5 36.0 37.0 37



MODELLED MIKE 11 WEIRS: OrchOrph_202210_V20

River and structure ID	Structure name	Physical location	Modelled structure type	Geometry (mRL NZVD2016, m)	Data source: Geometry	Weir type, valve regulation	Data source: type/regulation
Orchard Stream 2	TainuiStDiversionCulvert Added by T+T in model version OrchOrph_202210_v20. Not previously modelled.	35 Nikau Street	MIKE 11 weir (culvert overtopping structure)	Level-width table 18.30 mRL 0.50 m 18.59 mRL 1.45 m 18.60 mRL 6.50 m	As-builts NCC Plan No: 26-0634 23/11/2001	Broad Crested Weir; None	Default
Orchard Stream 3	NikauRdCulvertWEIR	30 / 35 Nikau Street	MIKE 11 weir (culvert overtopping structure)	Level-width table Minimum elevation: 18.1 mRL Maximum elevation: 18.39 mRL Width: 4.6 m	2021 LiDAR ¹	Broad Crested Weir; None	Default
Orchard Stream 4	11PolsteadCulvertWEIR	11 Polstead Road	MIKE 11 weir (culvert overtopping structure)	Level-width table Minimum elevation: 16.7 mRL Maximum elevation: 16.84 mRL Width: 4.0 m	2021 LIDAR ¹	Broad Crested Weir; None	Default
Orchard Stream 10	MarloweStCulvertWEIR	Marlowe Street	MIKE 11 weir (culvert overtopping structure)	Level-width table Minimum elevation: 11.1 mRL Maximum elevation: 11.35 mRL Width: 9.2 m	2021 LiDAR ¹	Broad Crested Weir; None	Default
Orphanage South 4	WoodfordCulvertWEIR	Woodford Lane	MIKE 11 weir (culvert overtopping structure)	Level-width table Minimum elevation: 44.7 mRL Maximum elevation: 45.5 mRL Width: 10.4 m	2021 LIDAR ¹	Broad Crested Weir; None	Default
Orphanage South 5	BridgewaterCulvertWEIR	Bridgewater Lane	MIKE 11 weir (culvert overtopping structure)	Level-width table Minimum elevation: 39.6 mRL Maximum elevation: 41.4 mRL Width: 21.1 m	2021 LiDAR ¹	Broad Crested Weir; None	Default
Orphanage Stream 4	OrphSaxtonRdCulvertWEIR	117 Saxton Road	MIKE 11 weir (culvert overtopping structure)	Level-width table Minimum elevation: 9.7 mRL Maximum elevation: 9.86 mRL Width: 22.2 m	2021 LiDAR ¹	Broad Crested Weir; None	Default
Orphanage Stream 6	SaxtonFieldPondWeir	Pond at Saxton Field, immediately upstream of Main Road Stoke	MIKE 11 weir	Cross Section Database ² 0 6.94 7.608 6.92 15.519 5.11 22.291 5.115 29.063 5.12 32.974 5.29 36.885 5.12 40.796 5.29 41.045 4.38 49.547 4.69 49.56 5.44	Orphanage model received from Stantec ³	Broad Crested Weir; None	Default

1: Weir geometry is simplified and uses 2021 LiDAR. LiDAR elevations at the road/bridge area excluded from the mesh (i.e. within the 1D model) are checked. Overtopping starts (0.1 m width) at the minimum elevation within this area, and extends to the full cross section / 1D extent width at the maximum elevation in the area. The MIKE 11 weir geometry is extended 5 m above the maximum 2021 LiDAR elevation in the mesh excluded area.

2: Models were originally built to NCC vertical datum. (NCC datum has a 12.07 m vertical offset from Nelson Vertical Datum NVD-55). To convert structure invert levels from source NCC datum to NZVD2016, a 12.4 m offset is applied (NZVD2016 = NCC Datum – 12.4), i.e. NZVD2016 levels are lower.

3: The Orchard and Orphanage models were originally built by MWH in 2016 (now Stantec). These were two separate models. As part of the model build, Staig & Smith undertook survey of structures in 2015. However, the total number of structures and the reported number of survey carried out is inconsistent. This means that it is unclear whether specific structures have or have not been surveyed. For the purpose of the flood modelling, it is assumed that structure information in the received models is accurate (i.e. likely from survey) unless there are inconsistencies with surrounding data.

Orchard Stream/Orphanage Stream catchment model

2D Hydraulic Structures

River	Structure ID	Physical location	Modelled structure type	Structure type		Modellec	l geometry ¹		Modelled structure moved outside of the 1d model area	Data source
	2021 Orph Stream Flood Wall Left bank chg1270 15.1		MIKE 21 Dike	Floodwall	Coord No.	х	Y	RL	No	As-builts
Orphanage		52 Kingsford			1	1618643	5425026	15.1		NCC Plan No: 26-0822
Stream		Drive, Stoke			2	1618637.19	5425042.269	15.13]	17/08/2021 Sheet 1
	2021 Orph Stream Flood Wall Left bank chg1640 10.1		MIKE 21 Dike	Floodwall	Coord No.	х	Y	RL	No	As-builts
Orphanage		117 Saxton			1	1618296.431	5424922.637	10.18		NCC Plan No: 26-0822
Stream		Road, Stoke			2	1618298.968	5424919.508	10.013]	17/08/2021 Sheet 3
	2016 Saxton Field North Bund Crest 7.56		MIKE 21 Dike	Stopbank	Coord No.	Х	Y	RL	Yes	As-builts
					1	1617977.317	5425043.691	7.56		NCC Plan No: 26-0782
Orphanage		Saxton Eiglds			2	1617990.09	5425045.63	7.56		Sheets 203/204
Stream		Suxton Fields			3	1618001.25	5425053.95	7.56		,
					4	1618015.32	5425060.8	7.56		
					5	1618036.95	5425071.53	7.56		
	2016 Saxton Field Bridge Wall 7.70		MIKE 21 Dike	Stopbank	Coord No.	х	Y	RL	Yes	As-builts
Orphanage		Saxton Fields			1	1617977.317	5425043.691	7.7		NCC Plan No: 26-0782
Stream					2	1617990.09	5425045.63	7.7		Sheet 204
	2016 Saxton Field South Ramp Stopbank 7.56		MIKE 21 Dike	Stopbank	Coord No.	х	Y	RL	Yes	As-builts
					1	1617961.051	5425029.498	7.56		NCC Plan No: 26-0782
Orphanage Stream		Saxton Fields			2	1617965.939	5425016.354	7.56		Sheets 204/205
					3	1617960.62	5424996.54	7.56		,
					4	1617959.39	5424993.79	7.56		
	2016 Saxton Field South Ramp Stopbank 7.66		MIKE 21 Dike	Stopbank	Coord No.	х	Y	RL	No	As-builts
					1	1617959.39	5424993.79	7.66		NCC Plan No: 26-0782
					2	1617946.326	5424987.471	7.66		Sheet 205
					3	1617902.713	5424952.983	7.66		
Orphanage		Saxton Fields			4	1617872.671	5424927.873	7.66		
Stream		Junton Fictus			5	1617872.721	5424925.908	7.66		
					6	1617847.687	5424904.191	7.66		
					7	1617848.695	5424900.018	7.66		
					8	1617848.745	5424893.017	7.66		
					9	1617801.65	5424853.074	7.66		

MODELLED MIKE 21 Dikes: OrchOrph_202210_V20

¹ Models were originally built to NCC vertical datum. (NCC datum has a 12.07 m vertical offset from Nelson Vertical Datum NVD-55). To convert structure levels from source NCC datum to NZVD2016, a 12.4 m offset is applied (NZVD2016 = NCC Datum – 12.4), i.e. NZVD2016 levels are lower.

River	Structure ID	Physical location	Modelled structure type	Structure type		Modelled geometry ¹		Modelled structure moved outside of the 1d model area	Data source
					10	1617770.018 5424827.788	7.66		
					11	1617762.966 5424822.852	7.66		
					12	1617758.886 5424821.946	7.66		
					13	1617757.879 5424815.901	7.66		
					14	1617762.815 5424809.907	7.66		
					15	1617818.221 5424750.572	7.66		

DRAWN

CHECKED

CHGR JUN.23

KBBB JUN.23

16/06/2023



CHGR KBBB 15/06/23

DATE

CHK

GIS

Richmond

LOCATION PLAI



Exceptional thinking together www.tonkintaylor.co.nz

0

First version

REV DESCRIPTIO

xts/870888/870888.0013/WorkingMaterial/GIS/FIGURES/20230615 - V20 2130 Q100/OrchOrph_202210_V20_TT_DH/2017_RCP8pt5M_2130_100Y_PoP_2D_Depth_2mGRID.mxd 2023-Jun-15 3:19:00 pm Drawn by CHGR

TITLE ORCHARD/ORPHANAGE MODEL RESULTS: FLOOD DEPTH 2130 RCP8.5M 1% AEP 'PEAK OF PEAKS'

0 No Issues Data Provided 1 Clarification required. Unlikely to alter results 2 Moderate Issue that may affect results Major Issue that will likely affect results

ltem	Category	Category	WSP Comments [Hydrology model 202205v5] [Hydraulic model version OrchOrph_202210_v19]	WSP Rating [Hydrology model 202205v5] [Hydraulic model version OrchOrph_202210_v19]	T+T Response [Hydrology model 202205v5 - i.e. unchanged] [Hydraulic model version OrchOrph_202210_v20]	WSP Comments [Hydrology model 202205v5] [Hydraulic model version OrchOrph_202210_v20]	WSP Rating [Hydrology model 202205v5] [Hydraulic model version OrchOrph_202210_v20]
INP-1	Model Data	Mike Flood files	All files provided for RCP8.5 2130 100yr ARI with durations of 1, 6, and 12	0	n/a	n/a	0
INP-2	Model Data	Mike 11 files	All files provided	0	n/a	n/a	0
INP-3	Model Data	Mike 21 files	All files provided	0	n/a	n/a	0
INP-4	Model Data	Mike Urban files	All files provided	0	n/a	n/a	0
INP-5	Report	Report	All files provided	0	n/a	n/a	0
INP-6	Results	1% AEP, 1hr duration for 2130 climate assuming RCP 8.5	All files provided	0	n/a	n/a	0
INP-7	Results	1% AEP, 6hr duration for 2130 climate assuming RCP 8.5	All files provided	0	n/a	n/a	0
INP-8	Results	1% AEP, 12hr duration for 2130 climate assuming RCP 8.5	All files provided	0	n/a	n/a	0

3

Hydrology	0	No Issues
	1	Clarification required. Unlikely to alter results
	2	Moderate Issue that may affect results
	3	Major Issue that will likely affect results

ltem	Category	Setting	WSP Comments (Hydrology model 202205v5)	WSP Rating (202205v5)	T+T Response (Hydrology model 202205v5 - i.e. unchanged)	WSP Comments (Hydrology model 202205v5) 1 minute time series	WSP Rating (202205v5) 1 minute time series
Hyd-1	Method	Curve Number	We recommend doing sensitivity test on curve number to see the impact on calculated runoff. Please discuss with NCC Engineering Manager for agreement on the hydrological parameters. Note that TP108 may not always be appropriate for catchments outside of Auckland	0	n/a	n/a	0
Hyd-2	Method	Time of Concentration (ToC)	Use of TP108 to determne TOC. Note that TP108 may not always be appropriate for catchments outside of Auckland	0	n/a	n/a	0
Hyd-3	Method	Update to MIKE URBAN hydrology	Has a result hydrograph comparison between the calibrated HEC-HMS model and the MU catchment hydrology been performed?	1	Yes. T+T are satisfied that the two model provide the same results.	[No action required]	0
Hyd-4	Method	Results and inputs to hydraulic model	Inputs to the hydraulic model use a time step of 5minutes. Memo mentions 1min time step. WSP has also been provided a version of hydraulic model inputs with 1minute time steps. It appears that there are two versions of the hydrology and the older (5minute) version of hydrology has been run in the hydraulic models.	3	Agreed. This is a filing error. 1 minute version has been used for the model. 5 minute timestep version has been removed [action taken].	[No further action required]	0

MIKE URBAN



Clarification required. Unlikely to alter results Moderate Issue that may affect results Major Issue that will likely affect results

ltem	Category	Setting	WSP Comments (Model version OrchOrph_202210_v19)	WSP Rating (OrchOrph_202210_v19)	T+T Response (Model version OrchOrph_202210_v20)	WSP Comments (Model version OrchOrph_202210_v20)	WSP Rating (OrchOrph_202210_v 20)
MUSetting-1	Roughness	Concrete Normal to 52.63 (0.019)	All pipes use Concrete Normal. Value has been increased	2	This is a legacy error from overtopping road weirs being	[No further action required]	0
		All others MU standard	from standard for all pipes and may affect results. Is there		set at n=0.019.		
			justification for the increase?		Roughness values have been lowered to n=0.015 in the		
					model. This has been set to be consistent with other		
					concrete structures within the model which also have		
					manning's n = 0.015 [action taken].		
MUSetting-2	BCs	6 Network Loads applied as inflow hydrographs	ОК	0	n/a	n/a	0
MUSetting-3	Network Sense	Longsection	One negative slope at PalmAvenue4 - confirm	1	Data sources of manhole inverts are Top of the South	Link TainuiStOverflow3_2 and MH D625704 have inconsistent invert levels.	1
		Manholes are sized appropriately	ОК		Maps (upstream) and as-builts (downstream).	Recommend using As-built status marker in MU if levels are correct.	
		Pipe diameters increase downstream			Without additional as-built or survey data, there is not		
					justification to change the network inverts. This has been		
					added to the list of future updates for the model [no		
					action].		
MUSetting-4	Head Loss	Types: Half Benching (0.3, Velocity Head)	ОК	0	n/a	n/a	0
		Inlet (Velocity Head)					
		Outfall (1, Velocity Head)					

T:\Nelson\Projects\870888\870888.0013\IssuedDocuments\2023-02-28 - To NCC - OrchOrph model V20_SETTINGUP\01 Model update memo and peer review table\Orchard-Orphanage_PeerReview_2023Feb_v0.4.xlsx

MIKE 11



Clarification required. Unlikely to alter results Moderate Issue that may affect results Major Issue that will likely affect results

Item	Category	Setting	WSP Comments	WSP Rating	T+T Response	WSP Comments	WSP Rating
M11Setting-1	Network	Max dx: Channel 5m Culverts 1000m	Max channel dx seems low. Where h points are close (around culverts/ assets/ etc) there is potential for instability.	2	Agreed, max dx initially chosen from testing of the 1D only model, which is not necessarily applicable to the coupled model. Max dx of Orphanage branches has been increased to 10m in the model. Note that testing indicating the max dx of 5m for Orchard Stream was okay laction taken!	[No further action required]	0
M11Setting-2	Network	Weirs: 7ea - Broadcrested. Varying levels and dimenstions.	Appear to be appropriately represented - have not checked Q/h relationships Head loss factors OK Levels and dimensions not verified	0	n/a	n/a	0
M11Setting-3	Network	Culverts: 22ea. Varying levels and dimensions. Losses 0.5 Inflow/ 1 outflow for all culverts Mannings values 0.013 (excluding WhakatuEstate 0.009)	 * Would be benefical to check headwalls * Have not verified Q/h relationships * Mannings values are low (0.013) (essentially always new) and especially when compared to pipe default Concrete (Normal) values (0.019). * Whakatu Estate Manning's value is 0.009, which seems very low * Check Whakatu Dr Estate Culvert (second culvert does not appear to be represented). * Many culverts in Whakatu Estate not represented under SH6 and may lead to overrepresentation of flood levels 	3	 Agreed, but out of scope of this project. Limitations around the hydraulic performance of structures has been noted and flagged for future improvements to the model [no action]. As above [no action]. Manning's n values for culverts have been set to n=0.015 and are now consistent with stormwater network pipes, i.e. represent some aging of the concrete. [no action]. This culvert was incorporated at the request of NCC using as-builts (2021) provided. Manning's n roughness is taken from product information for GRP pipe (refer to the provided 'structures' documentation for reference) [no action]. Single culvert was added at the request of NCC [no action]. Hydraulic connection between the floodplain and estuary is not within the scope of this project. This is at the request of NCC. These models are intended to represent flooding from streams only (i.e. no stormwater network.) Note that the Nelson/Tasman Land Development Manual assumes full blockage of culverts which are less than 1.5m diameter, which is consistent with not incorporating the culverts through SH6. T+T agree that not including these culverts is likely to impact on floodplain results. This model assumption has been documented for future model users [no action]. 	As updates to culverts is out of scope, [No further action required]. Recommend adding culvert checks to future model improvements.	0
M11Setting-4	Network	Energy loss: 5 loss factors in Orphanage Stream representing 90° bends	ОК	0	n/a	n/a	0
M11Setting-5	Network	Open Channels	Orchard Stream at Nikau Road appears to be represented incorrectly in M11 when queried with Google StreetView and aerial imagery. There's either a missing culvert in M11 or it is piped for longer than modelled. Others OK	1	Agreed, culverts have been added using provided model or Top of the South Maps only. As builts of this additional culvert have now been supplied. Additional culvert upstream of Nikau Street (<i>TainuiStDiversionCulvert</i>) has been added to model. Note that as-builts of the Tainui Street overflow (pipe network) were also provided and have been updated in the model. [action taken].	·[No further action required]	0
M11Setting-6	Boundary Conditions	Inflows applied as distributed source.	Appear OK. Boundary IDs/ MU catchments are random (not in sequential order), so it's difficult to visually link the catchment to the channel chainage. Doesn't change model results, but could be difficult for others to use/ update.	1	GIS files/map of subcatchments provided with model for ease of future use [no action].	[No action required]	0
M11Setting-7	Boundary Conditions	DSBC - 3WL- Tidal RCP8.5M 2130 Orch_Orchard Stream Orph_OrphanageStream Whakatu Estate Culvert	ОК	0	n/a	n/a	0
M11Setting-8	IC	WL 1.99, Q 0.1	OK	0	n/a	n/a	0
M11Setting-9	Std Resistance	30 (Not Used)	OK	0	n/a	n/a	0
M11Setting-11	vvave Approx	Resistance: Primarily 0.045	UN 0.045 = Main Channel, some weeds and stones (Chow	0	II/d It is havond the scope of this project to change manning's providence values in localized	II/d [No action required]	0
M11Setting-12	xs	Primarily interpreted from LiDAR	Some open channels look very overgrown. 0.045 Manning's value may be too low.	0	areas without additional validation data. Manning's n roughness values in localised from the original model build value of n=0.03 following testing by NCC/T+T [no action].	n/a	0
M11Setting-12	Other Settings	Timesten: Controlled by M21	OK	0	n/a	n/a	0
M115-cting-13		Save Timestep: 1min Engine: M11		0			0
ivi11Setting-14	Results	event		2	Agreed. Increasing the max dx of the branches has improved stability of the model [action taken].	[NO TURTNER ACTION REQUIRED]	0
M11Setting-15	Mike11.ini	WL_EXCEEDANCE_FACTOR = 10000	Potential to mask model instabilities. Should try lower values, eg 10	1	Exceedance factor has been reduced to 100 [action taken].	[No further action required]	0

```
MIKE 21
```

0 No Issues

Clarification required. Unlikely to alter results Moderate Issue that may affect results Major Issue that will likely affect results

Item	Category	Setting	WSP Comments (Model version OrchOrph_202210_v19)	WSP Rating (OrchOrph_202210_v19)	T+T Response (Model version OrchOrph 202210 v20)	WSP Comments (Model version OrchOrph 202210 v20)	WSP Rating (OrchOrph 202210 v20)
M21Setting-1	Domain	No Boundaries, Material, Infrastructure	ОК	0	n/a	n/a	0
M21Setting-2	Time	Timestep - 0.2s	ОК	0	n/a	n/a	0
M21Setting-3	Inland Flooding	Ticked on	ОК	0	n/a	n/a	0
M21Setting-4	Technique	High order	ОК	0	n/a	n/a	0
		Time step 0.2 - 0.01					
		CFL 0.9					
M21Setting-5	Depth	No DC	ОК	0	n/a	n/a	0
M21Setting-6	Flood Dry	Dry - 0.02	Higher than standard modelling values. May negate some	2	Agreed, values taken from outdated guidance.	Updated values seem low but do not appear to increase run times	0
		Wet 0.04	sheet flow		Dry/Flood/Wet have been lowered to recommended values	[No further action required]	
					0.0001/0.001/0.002 in the model [action taken].		
M21Setting-7	Density	Barotropic	ОК	0	n/a	n/a	0
M21Setting-8	Viscosity	Eddy: Smagorinsky	ОК	0	n/a	n/a	0
		Constant - 0.28					
		Min and Max OK					
M21Setting-9	Roughness	Mannings	ОК	0	n/a	n/a	0
M21Setting-10	Coriolis	None	ок	0	n/a	n/a	0
M21Setting-11	Ice	None	ОК	0	n/a	n/a	0
M21Setting-12	Tidal	None	ОК	0	n/a	n/a	0
M21Setting-13	Precipitation	None	ОК	0	n/a	n/a	0
M21Setting-14	Infiltration	None	ОК	0	n/a	n/a	0
M21Setting-15	Wave Radiation	None	ОК	0	n/a	n/a	0
M21Setting-16	Sources	None	ОК	0	n/a	n/a	0
M21Setting-17	Structures	4 Dikes	Saxton Field South Ramp 19.96 is partially outside of mesh	3	Agreed, dike has been digitised incorrectly.	All dikes digitised within domain and appear correct. Levels and locations not	0
			zone. Consequently, flooding appears to occur over and		All dikes have been check and updated using available information. A	verified	
			around this dike despite the water level being lower than the		table of 2D structures (similar to that of 1D structures) has been	[No further action required]	
			crest of the dike.		provided [action taken].		
			Unsure of why dike Saxton Field North Bund extends across				
			road				
			All other dikes appropriately incorporated. Levels and				
			locations have not been verified.				
			Possible missing culverts in Whakatu Estate (see				
			M11Setting_3)				
M21Setting-18	ICs	None	OK	0	n/a	n/a	0
M21Setting-19	BCs	All land boundary	OK	1	Hydraulic connection between the floodplain and estuary is not within	[No action required]	0
			A 2D boundary condition on the outside of SH6 may be		the scope of this project. This is at the request of NCC. These models		
			required if representing additional culverts in Whakatu Estate		are intended to represent flooding from streams only (i.e. no		
					stormwater network.) Note that the Nelson/Tasman Land		
					Development Manual assumes full blockage of culverts which are less		
					than 1.5m diameter, which is consistent with not incorporating the		
					culverts through SH6. T+T agree that not including these culverts is		
					likely to impact on floodplain results. This model assumption has been		
					documented for future model users [no action].		
M21Setting-20	Decoupling	None	ок	0	n/a	n/a	0
M21Setting-21	Outputs	Results	Saving timestep: 5min	0	n/a	n/a	0
			Separate Inundation file				

Item	Category	Setting	WSP Comments (Model version OrchOrph_202210_v19)	WSP Rating	T+T Response	WSP Comments [Hydrology model 202205v5] [Hydraulic model version OrchOrph_202210_v20]	WSP Rating
M21Input-1	Mesh		# of elements 1119257	0	n/a	n/a	0
M21Input-2	Mesh	Sizing	ОК	0	n/a	n/a	0

MIKE FLOOD

Item	Category	Setting	WSP Comments	WSP Rating	T+T Response	WSP Comments	WSP Rating
			(Model version OrchOrph_202210_v19)	(OrchOrph_202210_v19)	(Model version OrchOrph_202210_v20)	(Model version OrchOrph_202210_v20)	(OrchOrph_202210_v20)
MFSetting-1	Lateral Links	Type: Weir 1 Source: M21 (excepth Orph_OrphanageStream1240-1450 Left = M11)	ок	0	n/a	n/a	0
		Depth: 0.1 Weir Coefficient: 1.838					
MFSetting-2	Urban Links - M21 to Inlet	Max Flow - 0.05 for all Inlet area 0.08 Discharge Coefficient - 0.98 QdH factor - 0	OK, although the inlet area is small and may further decrease discharge between M21 and MU. Appears that weirs are used to represent most of the overflow from the SW network	0	n/a	n/a	0
MFSetting-3	Urban Links - Weir to M21	No settings	ОК	0	n/a	n/a	0
MFSetting-4	River/Urban Links	M11 water level and MU Outlet	ОК	0	n/a	n/a	0

Result Review Comments - 1% AEP, 12hr, 2120 (RCP8.5)



lt a ma	Catagon	Catting	W/CD Commonwhe	MCD Detine	TIT Deserves	MCD Comments	WCD Dating
item	Category	Setting	wsP comments	WSP Rating	I+I Kesponse	wsp comments	wsp Rating
			(Model version OrchOrph_202210_v19)	(OrchOrph_202210_v19)	(Model version OrchOrph_202210_v20)	(Model version OrchOrph_202210_v20)	(OrchOrph_202210_v20)
RES-1	Results	1D Result Stability	Some discharge wave propogation in lower reaches of Orphanage Sth Branch during 1-hr event. There are multiple	2	Agreed. Instabilities in 1D model have been improved by increasing	M11 Instabilities no longer present.	0
			waves of very high, low discharge. This could potentially cause discharge to the 2D surface		the max dx value to 10m.	Tainui Street instabilities significantly decreased.	
			Some issues around Tanui St Overflow		Note that there are remaining persistent instabilities located at Tainui	[No further action required]	
					Street Overflow which are associated with the M11-MU couplings.		
					These model issues/limitations have been documented for future		
					model users [action taken].		
RES-2	Results	2D Result Stability	ОК	0	n/a	n/a	0
RES-3	Results	Mass Balance	ОК	0	n/a	n/a	0

www.tonkintaylor.co.nz